

PRODUCT RANGE

AGRICULTURE





AGRICULTURE



	GRADE		TYPE	COLOR	PARTICLE SIZE	GENERAL DATA		MECHANICAL DATA								APPLICATION	OTHERS
						BA-CONTENT % INTERNAL	DENSITY AT 23°C	TENSILE STRENGTH AT BREAK, (MD/TD) MPA ISO 527-2	ELONGATION AT BREAK (MD/ TD) % ISO 527-2	MELT INDEX (MFI, 190°C/ 2,16 KG) G/10 MIN	MELTING POINT (°C) °C	ABSORP- TION ML/G	PH VALUE 1 % BY WEIGHT IN WA- TER %	MONO- MER CON- TENT	KALIUM CONTENT %		
	Plastics in agriculture	Lucofin 2033 DS	ЕВА	natural	granules	3	923	25/25	500/700	0,3	-	-	-	-	-		
Application		Lucofin 2133 VS	ЕВА	natural	granules	13	925	20/22	570/600	0,3	101	-	-	-	-		
		Lucofin 1083 DN	ЕВА	natural	granules	8	924	25/26	680/710	0,35	-	-	-	-	-		
	Plant growth	Lucoplant 205x	-	white	up to 5,00	-	0,56	8,0	770	-	-	≥ 350	6-7,5	≤ 500	≤ 17,8		
		Lucoplant 220x		white	up to 0,20-0,80	-	0,56	14,0	700	-	-	≥ 350	6-7,5	≤ 500	≤ 17,8		
		Lucoplant 230x	-	white	up to 0,30-1,00	-	0,56	12,0	800	-	-	≥ 350	6-7,5	≤ 500	≤ 17,8		



LOCATIONS



LUCOBIT Aktiengesellschaft
Basell Polyolefine GmbH / Brühler Str. 60 • B100
D-50389 Wesseling
Phone +49 2236 / 37859-0
Fax +49 2236 / 37859-99
info@lucobit.de
www.lucobit.com

Note

The information provided in this document is based on our product tests and present technical knowledge. It does not release purchasers from the responsibility of carrying out their receiving inspections. Neither does it imply any binding assurance of suitability of our products for a particular purpose. As LUCOBIT cannot anticipate or control the many different conditions under which this product may be processed and used this information does not relieve processors from their own tests and investigations. Any proprietary rights as well as existing legislation shall be observed.